

View Online at <https://aerobasegroup.com/nsn/5930-01-503-4279>

**Thread Class:**

2a single mounting facility

**Thread Pitch Diameters:**

+0.368/+0.374 inches single mounting facility

**Thread Length:**

0.427 inches single mounting facility

**Overall Length:**

2.216 inches

**Overall Diameter:**

1.150 inches

**Individual Section Quantity:**

2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

3.0 amperes inductive load ac at sea level and 3.0 amperes lamp load ac at sea level and 6.0 amperes resistive load ac at sea level

**Thread Tolerance Class:**

2a external single mounting facility

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0