# NSN 5930-01-503-4279

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-503-4279

## **Thread Class:**

2a single mounting facility

## **Thread Pitch Diameters:**

+0.368/+0.374 inches single mounting facility

## **Thread Length:**

0.427 inches single mounting facility

## **Overall Length:**

2.216 inches

## **Overall Diameter:**

1.150 inches

## Individual Section Quantity:

2

## Switch Contact Basic Design:

Nonpile-up symmetrical

### **Mounting Method:**

Threaded bushing single mounting facility

### Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.375 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

2 single actuator

# **Terminal Type:**

Tab, solder lug

## **Contact Load Current Rating:**

3.0 amperes inductive load ac at sea level and 3.0 amperes lamp load ac at sea level and 6.0 amperes resistive load ac at sea level

## **Thread Tolerance Class:**

2a external single mounting facility

## Style Designator:

Tap, circular, bushing mount

## **Thread Series Designator:**

Unef single mounting facility

## Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A052b0