# NSN 5930-01-504-6538

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-504-6538

#### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.437 inches single mounting facility

## **Overall Length:**

2.245 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.437 inches single actuator

## **Overall Diameter:**

1.162 inches

## Individual Section Quantity:

3

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

#### Throw Quantity:

2 each section rear

#### **Mounting Method:**

Threaded bushing w/panel seal single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-01-504-6538

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load dc at sea level Style Designator: Tap, circular, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0