NSN 5930-01-507-0503

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-507-0503

Thread Class:

Tilleau Olass.

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

2.747 inches

Overall Diameter:

1.036 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

1.00 amperes resistive load dc at sea level and 0.050 amperes inductive load dc at sea level

Precious Material And Location:

Plated contacts gold

Precious Material:

Gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-01-507-0503 Rotary Switch - Page 2 of 2



Fiig:

A052b0