

View Online at <https://aerobasegroup.com/nsn/5930-01-509-3446>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Body Diameter:**

0.500 inches

**Bushing Length:**

0.350 inches

**Body Length:**

0.415 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.420 inches

**Actuator Position-action Relationship:**

Up position maintained and center position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

Circuit iso assembly; w/s - seawolf calss ssn

**Mounting Surface To Terminal End Distance:**

0.570 inches

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive ac and 5.000 amperes resistive dc

**Special Features:**

50 micron inches of gold plating on contacts

**Precious Material And Location:**

Terminals gold and gold over silver terminals silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0