

View Online at <https://aerobasegroup.com/nsn/5930-01-509-3446>

Thread Class:

2a

Body Style:

Bushing mount

Body Diameter:

0.500 inches

Bushing Length:

0.350 inches

Body Length:

0.415 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.420 inches

Actuator Position-action Relationship:

Up position maintained and center position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Circuit iso assembly; w/s - seawolf calss ssn

Mounting Surface To Terminal End Distance:

0.570 inches

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive ac and 5.000 amperes resistive dc

Special Features:

50 micron inches of gold plating on contacts

Precious Material And Location:

Terminals gold and gold over silver terminals silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0