NSN 5930-01-509-4713

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-509-4713

| Overall Length: |
|---|
| 2.155 inches |
| Overall Width: |
| 1.281 inches |
| First Flat Length: |
| 0.250 inches single actuator |
| Shaft Diameter: |
| 0.250 inches single actuator |
| Shaft Length: |
| 0.437 inches single actuator |
| Overall Diameter: |
| 1.000 inches |
| Individual Section Quantity: |
| 4 |
| End Application: |
| Nsn 2040-01-498-0619, photon workstation; w/s - los angeles class ssn (688) |
| Pole Quantity: |
| 1 each section in-line |
| Throw Quantity: |
| 10 each section in-line |
| Mounting Method: |
| Threaded bushing single mounting facility |
| Contact Voltage Rating In Volts: |
| 115.0 highest ac voltage rating at altitude |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |
| Tab, solder lug |
| Switch Actuator Positioning Increment: |
| 22.5 degrees single actuator |
| Contact Load Current Rating: |
| 20.0 milliamperes resistive load highest ac voltage rating at altitude |
| Product Name: |
| Multi-deck rotary switch |
| Special Features: |
| Non-turn washer supplied with mounting hardware |
| Precious Material And Location: |
| Contacts and terminals gold and contacts and terminals silver |
| Precious Material: |
| Gold and silver |
| Style Designator: |
| Circular wafer, bushing mount |

NSN 5930-01-509-4713

Rotary Switch - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0