

View Online at <https://aerobasegroup.com/nsn/5930-01-509-5311>

Body Style:

Bushing mount

Bushing Length:

0.437 inches

Body Length:

0.843 inches

Body Width:

0.500 inches

Body Height:

0.350 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.225 inches

Actuator Style:

Round

Actuator Diameter:

0.218 inches

Actuator Height:

0.660 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc and 125.0 ac

Mounting Surface To Terminal End Distance:

0.571 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

4 pole, double throw, three positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes inductive dc and 5.000 amperes resistive dc

Special Features:

Reference number differentiating material will be iaw naval inventory control point activity hx quality control, manufacturing and testing specifications available at the dla icp.Item must comply with requirements of defense supply center philadelphia production standard no.Lo5162)

Precious Material And Location:

Contacts terminals gold and contacts terminals silver

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0