

View Online at <https://aerobasegroup.com/nsn/5930-01-509-5311>

**Body Style:**

Bushing mount

**Bushing Length:**

0.437 inches

**Body Length:**

0.843 inches

**Body Width:**

0.500 inches

**Body Height:**

0.350 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.225 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.218 inches

**Actuator Height:**

0.660 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc and 125.0 ac

**Mounting Surface To Terminal End Distance:**

0.571 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

4 pole, double throw, three positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes inductive dc and 5.000 amperes resistive dc

**Special Features:**

Reference number differentiating material will be iaw naval inventory control point activity hx quality control, manufacturing and testing specifications available at the dla icp.Item must comply with requirements of defense supply center philadelphia production standard no.Lo5162)

**Precious Material And Location:**

Contacts terminals gold and contacts terminals silver

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0