# NSN 5930-01-510-2510

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-510-2510

Th	read	d C	lass:

2b single mounting facility

#### **End Application:**

Control panel assembly; w/s - los angeles class ssn (688)

## **Mounting Method:**

Threaded hole single mounting facility

#### Thready Qty Per Inch (tpi):

24 single mounting facility

#### **Thread Size:**

0.190 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

120.0 ac at sea level

#### **Mounting Facility Pattern:**

Four position circular single mounting facility

#### **Switch Actuator Indexing Position Quantity:**

4 single actuator

# **Terminal Type:**

Tab w/screw

## **Contact Switching Action:**

Makes before breaks single section in-line

# **Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

#### **Product Name:**

Snap action rotary switch

# **Special Features:**

Mounting screws .190-24unc-2a (4) length and headstyle to suit application, screws not furnished

## **Style Designator:**

Tap, circuit selector

#### **Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unc single mounting facility

#### **Specification Data:**

81349-mil-s-15291/2 government specification

#### Shelf Life:

N/a

# **Unit Of Measure:**

\_

#### **Demilitarization:**

No

# Fiig:

A052b0