

View Online at <https://aerobasegroup.com/nsn/5930-01-510-2510>

Thread Class:

2b single mounting facility

End Application:

Control panel assembly; w/s - los angeles class ssn (688)

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks single section in-line

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Product Name:

Snap action rotary switch

Special Features:

Mounting screws .190-24unc-2a (4) length and headstyle to suit application, screws not furnished

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-s-15291/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0