

View Online at <https://aerobasegroup.com/nsn/5930-01-512-2128>

**Body Style:**

Panel mounted

**Body Length:**

2.812 inches

**Body Width:**

0.960 inches

**Body Height:**

1.200 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator and red single actuator

**Illuminated Actuator Color Sequence:**

Top half of actuator white, bottom half of actuator red

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Ic test swbd, imc ckt

**Mounting Surface To Terminal End Distance:**

0.250 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Special Features:**

4pdt; horizontal split; non-engraved lens

**Precious Material And Location:**

Contacts silver

**Test Data Document:**

81349-mil-prf-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 turret

**Specification Data:**

81349-mil-prf-22885/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0

**Mil-std (military Standard):**

Mil-prf-22885 spec.