NSN 5930-01-512-2128



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-512-2128 **Body Style:** Panel mounted **Body Length:** 2.812 inches **Body Width:** 0.960 inches **Body Height:** 1.200 inches **Actuator Color:** White single actuator **Illuminated Actuator Color:** White single actuator and red single actuator **Illuminated Actuator Color Sequence:** Top half of actuator white, bottom half of actuator red **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **End Application:** Ic test swbd, imc ckt **Mounting Surface To Terminal End Distance:** 0.250 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive ac **Special Features:** 4pdt; horizontal split; non-engraved lens **Precious Material And Location:** Contacts silver **Test Data Document:** 81349-mil-prf-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 4 turret **Specification Data:** 81349-mil-prf-22885/9 government specification Shelf Life:

No

N/a

Unit Of Measure:

Demilitarization:

NSN 5930-01-512-2128

Push Switch - Page 2 of 2



Fiig:

A053a0

Mil-std (military Standard):

Mil-prf-22885 spec.