## NSN 5930-01-512-2128

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-512-2128

Body Style: Panel mounted Body Length:

2.812 inches

Body Width:

0.960 inches

**Body Height:** 

1.200 inches

Actuator Color:

White single actuator

**Illuminated Actuator Color:** 

White single actuator and red single actuator

#### Illuminated Actuator Color Sequence:

Top half of actuator white, bottom half of actuator red

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Ic test swbd, imc ckt

#### Mounting Surface To Terminal End Distance:

0.250 inches

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

## Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

## **Special Features:**

4pdt; horizontal split; non-engraved lens

## **Precious Material And Location:**

Contacts silver

## Test Data Document:

81349-mil-prf-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

4 turret

#### **Specification Data:**

81349-mil-prf-22885/9 government specification

## Shelf Life:

N/a

Unit Of Measure:

--

- Demilitarization:
- No

# NSN 5930-01-512-2128

Push Switch - Page 2 of 2

**Fiig:** A053a0

Mil-std (military Standard):

Mil-prf-22885 spec.

