

View Online at <https://aerobasegroup.com/nsn/5930-01-512-4645>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof and watertight

**Bushing Length:**

0.470 inches

**Body Length:**

1.340 inches

**Body Width:**

1.660 inches

**Body Height:**

1.110 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.420 inches

**Actuator Height:**

1.140 inches

**Actuator Position-action Relationship:**

Center position maintained

**Actuator Position-locking Relationship:**

Center position locked out

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

1.370 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 12.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0