NSN 5930-01-514-7966

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-514-7966

Thread Class: 2a single mounting facility **Thread Length:** 0.250 inches single mounting facility **Overall Length:** 1.906 inches **Overall Diameter:** 1.313 inches **Individual Section Quantity: End Application:** Virginia class submarine **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section in-line **Mounting Method:** Threaded bushing single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 12 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** Adjustable stop single actuator **Contact Load Current Rating:** 1.5 amperes resistive load dc at sea level **Product Name:** Switch section, rotary **Special Features:**

Electrostat (cage 79692) p/n d4c0112n-l30a01b, as modified per drawing; non shorting contact type; ceramic insulation

Precious Material And Location:

Clips and rotors silver

NSN 5930-01-514-7966

Rotary Switch - Page 2 of 2



Precious Material:
Silver
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0