

View Online at <https://aerobasegroup.com/nsn/5930-01-514-7983>

**Overall Length:**

4.500 inches

**Outside Diameter:**

0.500 inches single connection

**End Application:**

Compressor

**Pressure Switch Type:**

Differential

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 165.0 degrees fahrenheit

**Proof Pressure:**

7000.00 pounds per square inch

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes inductive load second voltage and 5.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+430.00/+1700.00 actuation point pounds per square inch and +360.00/+1450.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point serrated nut and external deactuation point serrated nut

**Contact Stimulus Rating:**

360.00 differential point pounds per square inch and 1700.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

250.0 ac at sea level second voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Special Features:**

Nema 4 rated; tamper resistant screw; 12 inch wire leads

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0