

View Online at <https://aerobasegroup.com/nsn/5930-01-514-7983>

Overall Length:

4.500 inches

Outside Diameter:

0.500 inches single connection

End Application:

Compressor

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 165.0 degrees fahrenheit

Proof Pressure:

7000.00 pounds per square inch

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes inductive load second voltage and 5.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+430.00/+1700.00 actuation point pounds per square inch and +360.00/+1450.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point serrated nut and external deactuation point serrated nut

Contact Stimulus Rating:

360.00 differential point pounds per square inch and 1700.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

250.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded external single connection

Special Features:

Nema 4 rated; tamper resistant screw; 12 inch wire leads

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0