

View Online at <https://aerobasegroup.com/nsn/5930-01-516-6867>

Hazardous Locations/environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

End Application:

Various weapon systems

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section front

Throw Quantity:

2 single section front

Mounting Method:

Bracket single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, parallel flatted single actuator

Terminal Type:

Threaded stud

Contact Switching Action:

Breaks before makes single section front

Contact Load Current Rating:

30.0 amperes resistive load ac at sea level

Product Name:

Enclosed rotary switch

Special Features:

Supersedes navsea drawing 815-1197224; see specification, pg. 10, table ii; item includes two each indicator lights: mil-I-3661/65

Style Designator:

Tap, circular, bushing mount

Specification Data:

81349-mil-dtl-15743/13 government specification

Specification Or Standard:

849 symbol

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0