

View Online at <https://aerobasegroup.com/nsn/5930-01-517-5339>

**Thread Class:**

2b

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Body Diameter:**

Between 0.970 inches and 1.030 inches

**Bushing Length:**

Between 0.520 inches and 0.560 inches

**Body Length:**

2.600 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.400 inches and 0.440 inches

**Actuator Height:**

1.715 inches

**Actuator Position-action Relationship:**

Right position momentary and center position maintained and left position maintained

**Actuator Position-locking Relationship:**

Center position locked in and out

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

2350-01-436-0005; wsd: fighting vehicle systems, bradley (bfvs)

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Nonturn feature

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc

**Special Features:**

Keyway .072wx.031d, keyway to within .050 of shoulder; wire leads 20 gage cut min 72 in

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0