

View Online at <https://aerobasegroup.com/nsn/5930-01-517-5339>

Thread Class:

2b

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant

Body Diameter:

Between 0.970 inches and 1.030 inches

Bushing Length:

Between 0.520 inches and 0.560 inches

Body Length:

2.600 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.400 inches and 0.440 inches

Actuator Height:

1.715 inches

Actuator Position-action Relationship:

Right position momentary and center position maintained and left position maintained

Actuator Position-locking Relationship:

Center position locked in and out

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

2350-01-436-0005; wsd: fighting vehicle systems, bradley (bfvs)

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Nonturn feature

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc

Special Features:

Keyway .072wx.031d, keyway to within .050 of shoulder; wire leads 20 gage cut min 72 in

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0