NSN 5930-01-517-6020



Thermostatic Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-01-517-6020
Overall Length:
5.200 inches
Overall Height:
3.200 inches
Overall Width:
3.200 inches
Unthreaded Mounting Hole Diameter:
0.200 inches
Capillary Tube Length:
30.000 inches
Bulb Length:
3.100 inches
Longest Horizontal Distance Between Mounting Centers:
2.500 inches
Longest Vertical Distance Between Mounting Centers:
4.500 inches
End Application:
4210-01-486-1035; wsd: truck, heavy expanded mobility tactical (hemtt)
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 140.0 degrees fahrenheit
Mounting Method:
Unthreaded hole and base

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw and wire lead

Contact Load Current Rating:

22.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable

Contact Stimulus Rating:

37.00 deactuation point degrees fahrenheit and 43.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

125.00 ac at sea level third voltage

Media For Which Designed:

Gas or liquid

NSN 5930-01-517-6020

Thermostatic Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0