

View Online at <https://aerobasegroup.com/nsn/5930-01-519-2991>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

1.270 inches

Body Width:

0.635 inches

Body Height:

0.930 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position locked in and out and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.180 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 15.000 amperes resistive dc and 10.000 amperes inductive dc and 4.000 amperes lamp dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Specification Data:

96906-ms24658 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0