

View Online at <https://aerobasegroup.com/nsn/5930-01-519-4878>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

4.562 inches

**Overall Height:**

4.234 inches

**Overall Width:**

3.500 inches

**Body Length:**

4.562 inches

**Body Width:**

3.438 inches

**Distance Between Mounting Facility Centers:**

2.250 inches

**End Application:**

Lgm30g; t.O. 21mlgm30g-I-7-4

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and threaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

60.00 pounds per square inch gage

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

8.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+0.40/+18.00 actuation point pounds per square inch gage and +0.30/+16.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

External deactuation point screw and external deactuation point screw

**Contact Voltage Rating In Volts:**

32.0 dc at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0