

View Online at <https://aerobasegroup.com/nsn/5930-01-519-4878>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.562 inches

Overall Height:

4.234 inches

Overall Width:

3.500 inches

Body Length:

4.562 inches

Body Width:

3.438 inches

Distance Between Mounting Facility Centers:

2.250 inches

End Application:

Lgm30g; t.O. 21mlgm30g-I-7-4

Pressure Switch Type:

Gage

Mounting Method:

Bracket and threaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

8.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.40/+18.00 actuation point pounds per square inch gage and +0.30/+16.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

32.0 dc at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0