

View Online at <https://aerobasegroup.com/nsn/5930-01-519-6996>

Thread Class:

3b single mounting facility

Overall Length:

6.160 inches

Overall Height:

2.906 inches

Overall Width:

2.220 inches

Distance Between Mounting Facility Centers:

2.000 inches single mounting facility

Individual Section Quantity:

7

End Application:

Panel power distribution

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load lowest ac voltage rating at sea level

Special Features:

Pistol grip handle; spring return to normal position; positive positioning, maintained action detent mechanism

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, panel mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0