

View Online at <https://aerobasegroup.com/nsn/5930-01-521-7850>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant and moisture resistant and fungus resistant and salt spray resistant and explosion proof

Body Length:

1.510 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.630 inches

Actuator Style:

Rectangular

Actuator Height:

0.150 inches

Actuator Width:

0.630 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Green single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator black background with class-a nvis green lettering when lighted and bottom half of actuator black background with class-a nvis green lettering when lighted

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

C-130j hercules aircraft

Mounting Surface To Terminal End Distance:

Between 1.322 inches and 1.478 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Part name assigned by controlling agency - illuminator 2000, 5/8 inch square illuminated switch/annunciator; switch actuation travel 0.125 inch ; actuation force 5.0 pounds ; flexible pc pin terminals; lamp 5.0 volt 0.115 amp replaceable; material exposed surfaces - corrosion resistant steel with flat black chrome finish; operating temperature minus 55.0 to plus 85.0 degrees celsius; non-operating temperature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0