

View Online at <https://aerobasegroup.com/nsn/5930-01-521-7851>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant and moisture resistant and fungus resistant and salt spray resistant and explosion proof

**Body Length:**

1.510 inches

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Case Material:**

Metal

**Actuator Length:**

0.630 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.150 inches

**Actuator Width:**

0.630 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Green single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator black background with class-a nvis green lettering when lighted and bottom half of actuator black background with class-a nvis green lettering when lighted

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

C-130j hercules aircraft

**Mounting Surface To Terminal End Distance:**

Between 1.322 inches and 1.478 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 0.500 amperes inductive dc

**Special Features:**

Part name assigned by controlling agency - illuminator 2000, 5/8 inch square illuminated switch/annunciator; switch actuation travel 0.125 inch ; actuation force 5.0 pounds ; flexible pc pin terminals; lamp 5.0 volt 0.115 amp replaceable; material exposed surfaces - corrosion resistant steel with flat black chrome finish; operating temperature minus 55.0 to plus 85.0 degrees celsius; non-operating temperature

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0