NSN 5930-01-522-4891

Pressure Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-522-4891

Overall Length: 3.188 inches Overall Height: 5.250 inches Overall Width: 2.500 inches Body Length: 3.188 inches Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts: 125.0 ac at sea level single voltage
Overall Height: 5.250 inches Overall Width: 2.500 inches Body Length: 3.188 inches Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
5.250 inches Overall Width: 2.500 inches Body Length: 3.188 inches Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Overall Width: 2.500 inches Body Length: 3.188 inches Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
2.500 inches Body Length: 3.188 inches Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Body Length: 3.188 inches Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
3.188 inches Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Body Height: 3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
3.000 inches Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Pressure Switch Type: Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Differential Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Mounting Method: Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Inlet connection and outlet connection Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Contact Action Stimulus: Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Increase Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
1 pole, double throw, both positions maintained Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Terminal Type: Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Screw Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Contact Adjustability: Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Actuation point not adjustable, manual reset Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Contact Stimulus Rating: 10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
10.00 actuation point pounds per square inch Contact Voltage Rating In Volts:
Contact Voltage Rating In Volts:
125 0 ac at sea level single voltage
125.0 ac at sea level single voltage
Frequency In Hertz:
60.0 single voltage
Media For Which Designed:
Gas, liquefied
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.
Fiig:
A048b0