NSN 5930-01-522-5259



Rotary Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-522-5259 **Thread Class:** 2b single mounting facility **Overall Length:** 3.520 inches **Overall Height:** 1.740 inches **Overall Width:** 2.500 inches **Individual Section Quantity: End Application:** Moored training ship **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Bracket single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 440.0 highest ac voltage rating at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Terminal Type:** Tab w/screw **Contact Load Current Rating:** 750.0 milliamperes inductive load highest ac voltage rating at sea level **Product Name:** Selector switch flush mounted **Special Features:** Legend plate reads: run/stop in both center and clockwise positions; also labeled: sea water **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5930-01-522-5259

Rotary Switch - Page 2 of 2



Fiig:

A052b0