NSN 5930-01-522-5350

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-522-5350

Thread Class:

2b single mounting facility

Overall Length:

3.520 inches

Overall Height:

1.740 inches

Overall Width:

2.500 inches

Individual Section Quantity:

1

End Application:

Moored training ship

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Load Current Rating:

750.0 milliamperes inductive load highest ac voltage rating at sea level

Product Name:

Selector switch flush mounted

Special Features:

Legend plate reads: 'off' at the center position, and 'on' at the clockwise position; also reads 'alarm' at the bottom

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-01-522-5350 Rotary Switch - Page 2 of 2

Fiig: A052b0

