

View Online at <https://aerobasegroup.com/nsn/5930-01-522-6353>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.350 inches

Body Length:

0.500 inches

Body Width:

0.270 inches

Body Height:

0.350 inches

Case Material:

Metal

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.420 inches

Actuator Position-action Relationship:

Up position maintained and left position momentary and right position momentary

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.505 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Contacts gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0