

View Online at <https://aerobasegroup.com/nsn/5930-01-522-6589>

**Body Style:**

Panel mounted

**Body Length:**

3.060 inches

**Body Width:**

0.990 inches

**Body Height:**

0.740 inches

**Actuator Length:**

0.740 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.750 inches

**Actuator Width:**

0.990 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

Between 1.380 inches and 1.450 inches

**Inclosure Type:**

Fully enclosed

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac and 5.000 amperes resistive dc and 1.500 amperes lamp ac and 1.500 amperes lamp dc and 2.500 amperes inductive ac and 2.500 amperes inductive dc

**Special Features:**

Yactuation force 4.0 lbs max; actuation travel 3/16 inch ; switch contacts gold plated silver; mechanical life 100, 000 cycles; electrical life 25, 000 cycles; switch contact resistance 25 milliohm max; lamp contact resistance 1 ohm, max; dielectric withstanding voltage 1, 000 v rms; insulation resistance 1, 000 megohms min; vibration 10 g's to 500 hz; shock 75 g's, cond b; operating temp m55.0 to 71.0 degrees c; salt spray 96 hrs, cond a; moisture resistance 10 days; letters are black

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0