

View Online at <https://aerobasegroup.com/nsn/5930-01-522-9169>

Thread Class:

2a single mounting facility

Thread Length:

0.502 inches single mounting facility and 0.542 inches single mounting facility

Overall Diameter:

Between 2.228 inches and 2.294 inches

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

1.375 inches single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round all actuators

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Product Name:

Rotary keylock switch

Special Features:

44 series switch, hl style, 3 decks, 4 poles per deck, 2 positions per pole; non-shorting contacts; key removal positions a only; hardware one spanner nut and one lockwasher assembled with switch; two keys supplied with switch; stops set to permit rotation from pos number 1 to pos 2; all locks keyed alike; key to be stamped with keycode no shh591; steel internal tooth lock washer 0.030 thick, 1.950 maximum dia, cadmium plated per qq-p-416 class 2 type ii; black anodized aluminum knurled nut, 1.800 dia, 0.281 thick with 0.135 diameter pin holes 90 degrees apart

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0