NSN 5930-01-523-6396

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-523-6396

Thread Class:
2a single threaded stud
Overall Length:
0.884 inches
Overall Height:
0.722 inches
Body Diameter:
0.660 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -10.0 degrees fahrenheit and 400.0 degrees fahrenheit
Mounting Method:
Threaded stud
Thready Qty Per Inch (tpi):
32 single threaded stud
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches single threaded stud
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
Contact Load Current Rating: 2.0 amperes resistive load first voltage
2.0 amperes resistive load first voltage
2.0 amperes resistive load first voltage Contact Adjustability:
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating:
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz:
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed:
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas or liquid
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas or liquid Style Designator:
2.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 125.00 actuation point degrees fahrenheit and 130.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas or liquid Style Designator: Disc

N/a

NSN 5930-01-523-6396

Thermostatic Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0