NSN 5930-01-524-3008

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-524-3008 **Overall Length:** 4.344 inches **Overall Width:** 3.430 inches **Body Length:** 2.187 inches **Body Height:** 4.500 inches **Unthreaded Mounting Hole Diameter:** 0.203 inches **Distance Between Mounting Facility Centers:** 2.250 inches **Pressure Switch Type:** Differential **Mounting Method:** Unthreaded hole **Contact Action Stimulus:** Decrease **Proof Pressure:** 300.00 pounds per square inch **Thread Size:** 0.250 inches single pressure connection **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained **Terminal Type:** Screw **Contact Load Current Rating:** 10.0 amperes resistive load first voltage **Contact Adjustability:** Actuation point adjustable and deactuation point adjustable **Contact Adjustment Range:** +1.50/+144.80 actuation point pounds per square inch and +6.70/+150.00 deactuation point pounds per square inch **Contact Adjustment Type:** External actuation point screw and external deactuation point screw **Contact Stimulus Rating:** 3.70 actuation point degrees celsius

Contact Voltage Rating In Volts:

125.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/mounting lugs

NSN 5930-01-524-3008

Pressure Switch - Page 2 of 2



| Ī | hread | Series | Desig | nator: |
|---|-------|---------------|-------|--------|
| | | | | |

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0