

View Online at <https://aerobasegroup.com/nsn/5930-01-524-3008>

**Overall Length:**

4.344 inches

**Overall Width:**

3.430 inches

**Body Length:**

2.187 inches

**Body Height:**

4.500 inches

**Unthreaded Mounting Hole Diameter:**

0.203 inches

**Distance Between Mounting Facility Centers:**

2.250 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Unthreaded hole

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

300.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Screw

**Contact Load Current Rating:**

10.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+1.50/+144.80 actuation point pounds per square inch and +6.70/+150.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw and external deactuation point screw

**Contact Stimulus Rating:**

3.70 actuation point degrees celsius

**Contact Voltage Rating In Volts:**

125.0 dc at sea level second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/mounting lugs

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0