NSN 5930-01-524-5473

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-524-5473

To Length:

| Body Style: |
|--|
| Hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel |
| 0.250 inches |
| Body Length: |
| Between 0.866 inches and 0.886 inches |
| Body Width: |
| Between 0.326 inches and 0.366 inches |
| Body Height: |
| Between 0.590 inches and 0.610 inches |
| Actuator Style: |
| Round, flush |
| Actuator Diameter: |
| 0.078 inches |
| Actuator Height: |
| 0.050 inches |
| Maximum Voltage Rating In Volts: |
| 30.0 dc |
| End Application: |
| Reconnaissance vehicle fenner |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Screw |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| Between 5.0 ounces and 15.0 ounces |
| Actuator Movement: |
| 0.003 overtravel millimeters |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 2.000 amperes inductive dc |
| Precious Material And Location: |
| Contacts gold |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-01-524-5473

Sensitive Switch - Page 2 of 2



Fiig:

A053a0