

View Online at <https://aerobasegroup.com/nsn/5930-01-525-4517>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.938 inches

**Body Width:**

0.688 inches

**Body Height:**

0.844 inches

**Unthreaded Mounting Hole Diameter:**

0.141 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.094 inches

**Actuator Height:**

0.051 inches

**Actuator Free Position Height:**

0.645 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**End Application:**

Swbd 4h-6h dc power distribution switchboards (blown fuse indication circuit)

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Switch Release Force:**

2.5 ounces

**Switch Actuating Force:**

4.0 ounces

**Actuator Movement:**

Between 0.005 overtravel inches and 0.012 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive ac

**Special Features:**

This switch is a lower force switch, it only takes 4 oz to operate switch, the differential travel is lower, with a min/max of .0002-.0005 inches.

**Precious Material And Location:**

Fine silver contacts silver

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0