

View Online at <https://aerobasegroup.com/nsn/5930-01-525-4517>

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.844 inches

Unthreaded Mounting Hole Diameter:

0.141 inches

Actuator Style:

Round

Actuator Diameter:

0.094 inches

Actuator Height:

0.051 inches

Actuator Free Position Height:

0.645 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Swbd 4h-6h dc power distribution switchboards (blown fuse indication circuit)

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Switch Release Force:

2.5 ounces

Switch Actuating Force:

4.0 ounces

Actuator Movement:

Between 0.005 overtravel inches and 0.012 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Special Features:

This switch is a lower force switch, it only takes 4 oz to operate switch, the differential travel is lower, with a min/max of .0002-.0005 inches.

Precious Material And Location:

Fine silver contacts silver

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0