

View Online at <https://aerobasegroup.com/nsn/5930-01-525-8063>

Thread Class:

2a single mounting facility

Thread Length:

0.365 inches single mounting facility and 0.380 inches single mounting facility

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.370 inches single actuator and 0.385 inches single actuator

Overall Diameter:

1.380 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

3.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Contact Load Current Rating:

5.0 milliamperes resistive load highest dc voltage rating at sea level

Precious Material:

Gold and silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0