

View Online at <https://aerobasegroup.com/nsn/5930-01-526-8413>

**Hazardous Locations/environmental Protection:**

Explosion proof and weatherproof

**Overall Length:**

5.375 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.375 inches

**Longest Vertical Distance Between Mounting Centers:**

4.270 inches

**End Application:**

Sensor list

**Operating Temperature Rating:**

Between -4.0 degrees fahrenheit and 220.0 degrees fahrenheit

**Mounting Method:**

Bracket

**Features Provided:**

Mounting hardware

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1500.00 pounds per square inch gage

**Mounting Facility Pattern:**

Four position rectangular

**Terminal Type:**

Wire lead

**Contact Adjustability:**

Actuation point adjustable

**Special Features:**

Spresure switch assembly includes 1 mounting bracket, 1 bracket clamp, 2 screw, cap, socket head. 1 u-bolt, stainless steel, 2 screw, cap, 4 washer, flat. 4 washer, flat h1cl, 4 nut, hexagon. Also included is threadlocker 242.

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Gold contacts on snap switch. Gold

**Precious Material:**

Gold

**Style Designator:**

Cylindrical

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0