

View Online at <https://aerobasegroup.com/nsn/5930-01-526-8413>

Hazardous Locations/environmental Protection:

Explosion proof and weatherproof

Overall Length:

5.375 inches

Longest Horizontal Distance Between Mounting Centers:

3.375 inches

Longest Vertical Distance Between Mounting Centers:

4.270 inches

End Application:

Sensor list

Operating Temperature Rating:

Between -4.0 degrees fahrenheit and 220.0 degrees fahrenheit

Mounting Method:

Bracket

Features Provided:

Mounting hardware

Contact Action Stimulus:

Increase

Proof Pressure:

1500.00 pounds per square inch gage

Mounting Facility Pattern:

Four position rectangular

Terminal Type:

Wire lead

Contact Adjustability:

Actuation point adjustable

Special Features:

Spressure switch assembly includes 1 mounting bracket, 1 bracket clamp, 2 screw, cap, socket head. 1 u-bolt, stainless steel, 2 screw, cap, 4 washer, flat. 4 washer, flat hlcl, 4 nut, hexagon. Also included is threadlocker 242.

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Gold contacts on snap switch. Gold

Precious Material:

Gold

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0