## NSN 5930-01-528-1437

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-528-1437 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 22.2 millimeters **Body Length:** 33.0 millimeters **Body Width:** 10.3 millimeters **Body Height:** 15.9 millimeters **Unthreaded Mounting Hole Diameter:** 3.1 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 3.1 millimeters **Switch Actuator Quantity: Actuator Length:** 20.1 millimeters **Actuator Style:** Roller arm **Actuator Free Position Height:** 20.7 millimeters **Actuator Roller Diameter:** 4.8 millimeters **Actuator Roller Width:** 4.8 millimeters **Maximum Voltage Rating In Volts:** 125.0 ac **End Application:** Hyster forklift **Inclosure Type:** Hermetically sealed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action single switch unit **Switch Release Force:** 20.0 grams **Switch Actuating Force:** 

200.0 grams

## **Actuator Movement:**

1.6 pretravel millimeters and 0.8 overtravel millimeters

## NSN 5930-01-528-1437

Sensitive Switch - Page 2 of 2



	Contact Load	Current F	Rating A	At Maximum	Rated \	Voltage:
--	--------------	-----------	----------	------------	---------	----------

0.100 amperes resistive ac

**Terminal Type And Quantity:** 

3 tab, solder lug

.

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A053a0