NSN 5930-01-531-7515

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-531-7515

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.203 inches
Overall Height:
0.605 inches
Body Diameter:
0.605 inches
Body Height:
0.290 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
0.937 inches
End Application:
Nsn 6115-01-296-1463; generator set, diesel engine
Tempurature Sensing Element Type:
Disc
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 550.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
7.0 amperes resistive load third voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Voltage Rating In Volts:
30.0 dc at sea level third voltage
Special Features:
Nickel plated copper terminals; salt spray resistance: 5%
Media For Which Designed:

Gas or liquid

NSN 5930-01-531-7515

Thermostatic Switch - Page 2 of 2



Precious Material And Location:
Contacts silver
Precious Material:
Silver
Style Designator:
Disc w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0