

View Online at <https://aerobasegroup.com/nsn/5930-01-533-8821>

Body Style:

Panel mounted

Body Width:

0.750 inches

Body Height:

0.750 inches

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

1.742 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc

Special Features:

Eled circuit configurations: each pushbutton cap contains 16 leds, 4 per quadrant, and all the electronics necessary for display illumination. The led circuit is either a single circuit with one common, g (style 1) or it is a horizontal split circuit with two commons, g and f (style 2). Each quadrant has its own i/o labeled a, b, c and d according to the quadrant it illuminates. Each quadrant has its own independent electronic circuit consisting of 4 leds and the driver, dimming and protection circuit (ddpc) needed for their operation. The led circuit can be either 28 vdc common anode (current sinking) or 28 vdc common cathode (current sourcing). Polarity is referenced with respect to commons g and f.

Terminal Type And Quantity:

6 crimp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0