## NSN 5930-01-534-7060

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-534-7060 **Thread Class:** 2a single mounting facility **Overall Length:** 1.430 inches **Overall Diameter:** 1.036 inches **Individual Section Quantity:** 2 **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Pole Quantity:** 6 each section front **Throw Quantity:** 2 each section front **Mounting Method:** Threaded bushing w/panel seal single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 2 all actuators **Terminal Type:** Pin **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 30.0 degrees all actuators **Contact Load Current Rating:** 10.0 amperes resistive load dc at sea level **Special Features:** Totally enclosed; op temp m65 to p125 degrees c; 5 in/lb maximum torque **Style Designator:** Circular wafer, panel mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5930-01-534-7060

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0