NSN 5930-01-536-9838

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-536-9838

Overall Length:

Between 1.140 inches and 1.260 inches

Overall Height:

Between 0.635 inches and 0.690 inches

Body Diameter:

0.640 inches

Body Height:

Between 0.366 inches and 0.431 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.147 inches

Tempurature Sensing Element Type:

Internal sensor

Operating Tempurature Rating:

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

120.00 actuation point degrees fahrenheit and 100.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Product Name:

Thermostatic switch

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc w/flange

Specification Data:

81349 - mil-prf-24236/24 government specification

Shelf Life:

N/a

NSN 5930-01-536-9838

Thermostatic Switch - Page 2 of 2



 :4	\sim	Measure:
 nit	()T	MESCIILE.

--

Demilitarization:

No

Fiig:

A048b0

Mil-std (military Standard):

Mil-prf-24236 spec.