

View Online at <https://aerobasegroup.com/nsn/5930-01-536-9910>

**Overall Length:**

Between 1.140 inches and 1.260 inches

**Overall Height:**

Between 0.635 inches and 0.690 inches

**Body Diameter:**

0.640 inches

**Body Height:**

Between 0.366 inches and 0.431 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.133 inches and 0.147 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

130.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Product Name:**

Thermostatic switch

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc w/flange

**Specification Data:**

81349 - mil-prf-24236/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0

**Mil-std (military Standard):**

Mil-prf-24236 spec.