

View Online at <https://aerobasegroup.com/nsn/5930-01-536-9933>

Thread Class:

2a single threaded stud

Overall Height:

Between 0.590 inches and 0.604 inches

Body Height:

0.437 inches

Overall Diameter:

0.640 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32 single threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 0.5 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

110.00 actuation point degrees fahrenheit and 90.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Product Name:

Thermostatic switch

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Disc

Thread Series Designator:

Unc single threaded stud

Specification Data:

81349 - mil-prf-24236/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0

Mil-std (military Standard):

Mil-prf-24236 spec.